

Hot Tub Record Sheet

| Week of: | |
|----------|--|
| | |

| Bather Load *Max # | Total CI (ppm) | Free CI 3 - 5.0 ppm | Combined CI** ≤ 0.5 ppm | pH 7.2 – 7.8 | Pool Clarity & Temp ≤104°F/ 40°C | Total Alkalinity 80 -120 ppm Calcium Hardness 180 - 220 ppm Cyanuric Acid 30 - 50 ppm Test these Weekly | Remarks: Chemicals added (eg: Backwash Filter, Drain pool, Vacuum pool, Add make-up water, etc.) | Initial |
|--------------------------|-------------------|---------------------------|-------------------------------|--------------------|--|--|---|---|
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | Load | Load (ppm) | Load (ppm) CI | Load (ppm) CI CI** | Load (ppm) CI CI** 7.2 - 7.8 | Load (<i>ppm</i>) CI CI** 7.2 - 7.8 Temp | Load (ppm) CI CI** 7.2 - 7.8 Temp Calcium Hardness 180 - 220 ppm *Max # 3 - 5.0 ppm ≤ 0.5 ppm ≤104°F/40°C Cyanuric Acid 30 - 50 ppm | Load (ppm) CI CI** 7.2 - 7.8 Temp Calcium Hardness 180 - 220 ppm (eg: Backwash Filter, *Max # 3 - 5.0 ppm ≤ 0.5 ppm ≤ 104°F/ 40°C Cyanuric Acid 30 - 50 ppm Drain pool, Vacuum pool, |

^{*}Maximum Bather load calculated on pool size Comments:

^{**}Combined CI = Total CI - Free CI